



Xactrol<sup>®</sup> Severe Service Control Valves



# **Xactrol**®

Severe Service Control Valve ANSI/ASME 150-4500#, 1/2 - 36"

ValvTechnologies Xactrol® severe service control valves are engineered for applications where minimum flow and relatively high differential pressures are required. They provide "exact" flow control solution every time, from minimum or normal control to full rangeability across a wide range of pressure drops and conditions.

## Xactrol® - Engineered for precision.

The Xactrol® product group unites Valvtechnologies' zero-leakage technology with special designs that allow rotary modulating control. From the Mark I design that features a characterized upstream seat, to the Mark III's precision engineered stacked disks, the Xactrol® allows the customer to combine precise flow control with tight shutoff.





## **Product Information**

## **Applications**

The Xactrol® control valve is typically used in applications where minimum flow and relatively high differential pressures are encountered:

- Power: Continuous blowdown, boiler feedpump recirculating bypass, main steam start-up vent
- Process: Pump outlet flow control, tank level control valve
- Mining: Make-up water control, dilution water control, process water isolation and control

Available Designs			
Mark I	Mark II	Mark III	
1/2 - 36", ANSI/ASME 150 - 4500	1/2 - 36", ANSI/ASME 150 - 4500	1/2 - 36", ANSI/ASME 150 - 4500	
Designed for minimum/normal flow control conditions	Designed for minimum/normal flow control conditions	Designed for minimum/normal flow control conditions	
Variety of characterized upstream seats available	Variety of characterized upstream seats available	Variety of characterized upstream seats available	
Engineered to meet your control needs	Engineered to meet your control needs	Engineered to meet your control needs	
Zero-leakage	Zero-leakage	Zero-leakage	
	Includes a second flow port designed to handle continuous minimum flow conditions	For applications requiring very high pressure drops	
		Includes a series of upstream pressure reducing plates	
		For the most difficult control applications	

## **Common Configurations:**



automated control valves



manual isolation valves

Superior failure resistance and reliability.











From simple minimum or normal flow control to full rangeability over a wide range of pressure drops and conditions, we have the solution for you.

Our Xactrol® Mark I is designed for minimum or normal flow control conditions as is experienced in a large number of flow control applications. The Mark I comes with a variety of characterized upstream seats, which can be specifically engineered/designed to suit your control needs.

The next step is the Mark II (see page 3). In addition to the normal flow conditions, the Mark II has a second flow port through the ball which is designed to handle your continuous minimum flow conditions.

For applications where very high-pressure drops are required, we offer the Mark III (see page 3), which has a series of upstream pressure reducing plates. The plates will successfully reduce, stage by stage, the pressure in the system, which when combined with the full rangeability of control through the control ball and seat, will solve the toughest of control applications.









Each valve package will come complete with its own flow test curve to ensure complete reliability. The above graph is from an actual flow loop test as supplied to the customer.



#### **Specifications**

EPP100 SR EEx " ib" for single acting actuators EPP100 DA EEx " ib" for double acting actuators

#### 2-Wire Current Loop Control

The control signal is a "real" 2-wire 4-20 mA current loop, with power and control signal in the same loop. If loop failure occurs, then the valve returns to failsafe position.

#### 4-20 mA Feedback Signal

#### Actuators

Controller available for double acting and spring return pneumatic actuators.

#### **Auto Calibration**

The self calibration routine sets all the basic settings and measures the actuator size for optimum valve control and fast feedback loop.

#### Low Air Consumption

Air is only used when it is needed providing significant savings in instrument air costs.

#### **Valve Flow Characteristics**

Choice of integrated standard valve curve characteristics for ball control valves (equal percentage).

#### **Manual Setpoint**

In service situations the setpoint can be manually chosen from the user menu.

#### Four Button Control Panel

The four button control panel makes each command sequence simple and easy to follow.

#### **Mechanical Stability**

The compact design with few moving parts is insensitive to environmental influences providing a high degree of immunity from failure.

#### **Digital Communication**

Up to 32 units can be linked via RS 485 communication interface to a PC or laptop computer for configuration and remote control.

#### **Digital LCD Display**

The two lines of 16 digit alphanumeric display.

#### **Power Failure Options**

If power fails the controller will close the actuator. When power returns the controller will restart and regulate again with no loss of data and configuration.

#### **Diagnostic Alarms**

Internal diagnostic alarm is activated in the event of air failure or if the control valve does not operate and the local LCD display will show an error message.



**Intelligent Valve Controller** 

Technical S	pecifications	
Control Signal	2 wire 4 - 20 mA, 18-24V	
Feedback Signal	4-20 mA, passive transmitter	
Operating Temp Range	21.6 -183.6 F°	
Hysteresis	0.80%	
Linearity	<1%	
Sensitivity	0.40%	
Air Supply	0 - 100 psi (0 - 7 Bar)	
Air Consumption	@0	
Air Flow	50 l/min	
Air Filtering	<30 um	
Air Entry	1/4" NPT	
Electrical Entry	2 x M20, 1.5 mm2	
Dimensions	L x B x H = 5.9 X 5.9 X 3.94″	
Housing Stainless Steel	316 ss	
Ingress Protection	IP 65	
Weight	4.185 lbs.	
Maximum Rotation	300°	



### Dynamics of a Mark III Xactrol® Control Valve

Upstream pressure reducing plates are stacked so maximum flow (pressure) travels through plate A (Fig. 3) then splits and pressure continues to be reduced as flow proceeds to follow tortuous 90° paths through succeeding holes in various stacked pressure reducing plates. See plates B, C & D (Fig. 3).

Multi-stage pressure reducing plates are positioned such that the diverging streams through the various plates actually collide with each other – greatly reducing their energy – before entering the next plate (Fig. 1).

Pressure reduction is at the upstream side of the valve, thus reducing the torque required to open and close the valve.

Downstream sealing face is protected from flow, thus offering repeatable zero-leakage.



Figure 1



Figure 3



## **Features and Benefits**

ValvTechnologies is committed to excellence in the design, manufacturing, service and testing of its Xactrol® severe service control valves, while providing control solutions to meet and exceed customer expectations.

Xactrol® Features and Benefits		
Features	Benefits	
Superior failure resistance and reliability	Enhanced process safety	
Constant packing load maintained with four-stud, live-loaded packing assembly	Increased safety, enhanced process effi- ciency, environmentally friendly	
Real flexibility in application, from 2" - 4"	Increased process efficiency	
Custom engineered	Process optimization	
Consistent flow-rates	Reduced fluid costs	
Control trim made from extremely hard components	Reduced wear, increased life of the valve	
Zero-leakage	Enhanced process safety, increased effi- ciency	
Resistance to small entrained solids	Lower maintenance costs, increased reliability	
Resistance to small entrained solids	Lower maintenance costs, increased reliability	

Precise flow control. Zero-leakage. All in a single unit.







# **Zero-leakage Valve Solutions**







## Worldwide Office Locations

Headquarters & Manufacturing ValvTechnologies, Inc. 5904 Bingle Road Houston, Texas 77092 U.S.A. Telephone +1 713 860 0400 Fax +1 713 860 0499 info@valv.com

To locate a distributor or satellite office near you, visit us online at: www.valv.com.

To contact sales anywhere in the world, email sales@valv.com

Peru Lima peru@valv.com

Brazil São Paulo brazil@valv.com

United Kingdom Stockton-on-Tees europe@valv.com

Australia Brisbane australia@valv.com China Shanghai china@valv.com

China Chengdu china@valv.com

China Beijing china@valv.com

Eastern Europe Warsaw poland@valv.com Middle East Dubai middle.east@valv.com

> India Chennai india@valv.com

Japan/Korea Seoul korea@valv.com

Spain Madrid spain@valv.com